

## Characteristics



- Can be used in the Pharmaceutical industry when equipped with a stainless steel SAE Type 304 4-wheel dolly or tilting cart
- Designed for the recovery of acids and corrosive liquids
- Heavy duty 2-stage by-pass motor
- Available with a variety of activated carbon, including KINA 3® activated carbon for the adsorption of chloride and acid vapors (HF, HCL, etc). Other types of activated carbon are available. Carbon cartridges must be ordered separately - not included
- For liquid recovery
- Acid-resistant polyethylene, nylon and PVC
- Available with a 4-wheel dolly, tilting cart, or hydro-cart
- 4-wheel dolly, and tilting cart available in stainless steel
- Includes a complete tool kit.

## Specifications

2D-ARU-15 SERIES	111429B	111429C	111429D	111429E	111430B	111430C
<b>Model Name</b>	2D-ARU-15 (TC) MRAC	2D-ARU-15 (TC) MRAC	2D-ARU-15 (TC) MRAC	2D-ARU-15 (TC) MRAC	2D-ARU-15 STD (HY-C) MRAC	2D-ARU-15 STD (HY-C) MRAC
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric	Electric	Electric
<b>Tension</b>	240 V	240 V	240 V	240 V	240 V	240 V
<b>Frequency</b>	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
<b>Phase</b>	Single	Single	Single	Single	Single	Single
<b>Wattage</b>	1050 W	1050 W	1050 W	1050 W	1050 W	1050 W
<b>Power</b>	1 kW	1 kW	1 kW	1 kW	1 kW	1 kW
<b>Amperage</b>	5 A	5 A	5 A	5 A	5 A	5 A
<b>Air Flow</b>	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O
<b>Type of Power Outlet</b>	European	UK	Swiss	Chinese	European	UK
<b>Suction Inlet</b>	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
<b>Cart Type</b>	Tilt Cart (TC)	Tilt Cart (TC)	Tilt Cart (TC)	Tilt Cart (TC)	Hydro Cart (HYC)	Hydro Cart (HYC)
<b>Filter Cleaning</b>	None	None	None	None	None	None
<b>Liquid Recovery Capacity</b>	47.3 L	47.3 L	47.3 L	47.3 L	47.3 L	47.3 L
<b>Length</b>	69 cm	69 cm	69 cm	69 cm	124 cm	124 cm
<b>Width</b>	76 cm	76 cm	76 cm	76 cm	51 cm	51 cm
<b>Height</b>	122 cm	122 cm	122 cm	122 cm	130 cm	130 cm
<b>Weight (Vacuum Only)</b>	48 kg.	48 kg.	48 kg.	48 kg.	113 kg.	113 kg.
<b>Cord Length</b>	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m
2D-ARU-15 SERIES	111430D	111430E				
<b>Model Name</b>	2D-ARU-15 STD (HY-C) MRAC	2D-ARU-15 STD (HY-C) MRAC				
<b>Type (Powerhead)</b>	Electric	Electric				
<b>Tension</b>	240 V	240 V				
<b>Frequency</b>	50 Hz	50 Hz				
<b>Phase</b>	Single	Single				
<b>Wattage</b>	1050 W	1050 W				
<b>Power</b>	1 kW	1 kW				
<b>Amperage</b>	5 A	5 A				
<b>Air Flow</b>	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h				
<b>Vacuum Pressure</b>	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O				
<b>Type of Power Outlet</b>	Swiss	Chinese				
<b>Suction Inlet</b>	38 mm	38 mm				
<b>Cart Type</b>	Hydro Cart (HYC)	Hydro Cart (HYC)				

<b>Filter Cleaning</b>	None	None
<b>Liquid Recovery Capacity</b>	47.3 L	47.3 L
<b>Length</b>	124 cm	124 cm
<b>Width</b>	51 cm	51 cm
<b>Height</b>	130 cm	130 cm
<b>Weight (Vacuum Only)</b>	113 kg.	113 kg.
<b>Cord Length</b>	10.6 m	10.6 m

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



ARU STD Tools and Accessories - Included



Liquid Filter - Included



Activated Carbon Cartridge - Optional



2D-ARU-15 STD (HY-C) MRAC