



EasyReach Cleaning Pad

Knitted polyester cover saturated with 70% USP IPA, 30% DI Water

Description

These presaturated covers for the EasyReach Cleaning Tool use a multi-layer quilted polyester fabric construction to form a clean, strong and durable cleaning pad, with excellent solvent holding and delivery capacity. The cleaning pads have no exposed edges, are abrasion and chemical resistant, and are extremely low in particles and fibers. These covers are saturated with a blend of 70% IPA and 30% DI Water.

Technical Data

Cover material	100% knitted polyester	
Cover construction	2-layer, ultrasonically bonded, laser sealed edges	
Solution of saturation; (blend ratio and constituents)	70% USP isopropanol, 30% deionized water	
Attribute, wipe; (units)	Value **	Test Method
Basis weight; nominal (g/m ²)	240	Contec Method
Specific ions		IEST-RP-CC004.3, Sec. 7.2.2
Sodium; (ppm)	0.05	
Chloride; (ppm)	0.03	
Silicone; (ppm)	ND	
Particles, readily releasable		IEST-RP-CC004.2, Sec. 5.1
P ≥ 0.5µm; (x10 ⁶ /m ²)	3.25	
Fibers > 100µm; (x10 ³ /m ²)	0.22	IEST-RP-CC004.2, Sec. 5.2
Saturation volume tolerance;		N/A
< 300 mL	+/- 12%	
300 -1666 mL	+/- 3%	
> 1666 mL	+/- 50 mL	

** ND = None detected; levels are below detection limit of test equipment

Part Number	Description	EA/PCH	PCH/OB1	OB1/CS	EA/CS
PSME0001	EasyReach Cleaning Pads, quilted polyester, presaturated with 70% USP IPA, sterile	8	4	2	64

Key: EA = Each, PCH = Pouch, OB1 = Outer Bag 1, CS = Case

Notes:

- 1) The information presented here is applicable to the part numbers shown above, as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details. Data shown are typical values and should not be used as product specifications.
- 2) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- 3) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Revision date: 07/01/15

